

42390P16990

Amendments to the Claims

1(Currently amended). A method of implementing the a Viterbi algorithm comprising:

calculating branch metrics for branches of ~~the~~ a Viterbi trellis;

combining the branch metrics with old path metrics to produce candidate path metrics;

selecting a new path metric associated with a selected trellis path for each state in the Viterbi trellis from the candidate path metrics; and

composing an optimal path value for each state in the Viterbi trellis, the optimal path value indicating multiple transitions of the selected trellis path.

2(Currently amended). The method of Claim 1 wherein the optimal path value ~~is comprised of~~ comprises optimal path value fragments.

3(Original). The method of Claim 2 wherein the optimal path value fragments are stored in memory blocks.

4(Original). The method of Claim 1 further comprising using the optimal path value to determine an output value.

5(Currently amended). The method of Claim ~~4~~ 1 wherein the optimal path value for the a lowest state of the Viterbi trellis at ~~the~~ an end of a memory block ~~of symbols indicates the transmitted symbols in the block.~~

6(Canceled).

7(Canceled).

8(Canceled).

42390P16990

⁶
~~9~~(Currently amended). The method of Claim 1 wherein further including
using a traceback pointer is used to select between two prior optimal path
values.

⁷
~~10~~(Currently amended). The method of Claim ⁶~~9~~ wherein the further
including selecting an old optimal path ^{value} ~~values are selected from the optimal~~
path values value for states a state that can transition transitions into a current
state.

11(Canceled).

⁸
~~12~~(Currently amended). The method of Claim 1 wherein the Viterbi
algorithm is implemented in by a reconfigurable chip.

⁹
~~13~~(Currently amended). The method of Claim 1 wherein selecting the
new path metric selecting and composing the optimal path value composing
steps operate in parallel.

42390P16890

¹⁰
14(Currently amended). An apparatus to implement the a Viterbi algorithm comprising:

a path metric storage adapted to store a path metric associated with a selected trellis path for each state in the a Viterbi trellis;

a path update unit adapted to update each path metric;

an optimal path value storage adapted to store an optimal path value for each state in the Viterbi trellis, the optimal path value indicating multiple transitions of the selected trellis path; and

a an optimal path value update unit adapted to update each optimal path value.

¹¹
15(Currently amended). The apparatus of Claim ¹⁰14 further comprising an output unit ~~adapted to use an optimal path value~~ to determine an output value for the Viterbi algorithm.

¹²
16(Currently amended). The apparatus of Claim ¹¹15 wherein the output value ~~produces~~ is the optimal path value for the state with the a lowest path metric.

17(Canceled).

¹³
18(Currently amended). The apparatus of Claim ¹⁰14 wherein the path metric update unit and the optimal path value update ~~operates~~ unit operate in parallel.

¹⁴
19(Currently amended). The apparatus of Claim ¹⁰14 ~~implemented on wherein the Viterbi algorithm is computed using reconfigurable logic~~.

¹⁵
20(Currently amended). The apparatus of Claim ¹⁴19 wherein the optimal path updating value update unit uses resources not ~~required for~~ used by the path metric update unit.

42390P16990

^{Cancelled}
21(~~Currently amended~~). The apparatus of Claim 14 wherein there is no
serial traceback operation ~~is required~~.

¹⁶
22(~~Currently amended~~). The apparatus of Claim ¹⁶14 wherein the optimal
path value storage ~~is separated into~~ includes multiple memory blocks.

¹⁷
23(~~Currently amended~~). The apparatus of Claim ¹⁶22 wherein the optimal
path value comprises optimal path fragments stored in the multiple memory
blocks.

¹⁸
24(~~Currently amended~~). The apparatus of Claim ¹⁷23 wherein the
optimal path value ~~updating unit operates on~~ update unit operates on the
optimal path value fragments to update the optimal path value.

¹⁹
25(~~Original~~). The apparatus of Claim ¹⁷23 wherein, during the readback
operation, the optimal path fragment from one memory block is used to
determine a pointer to an optimal path fragment in another memory block.

42390P16990

Cancelled

26(New). A method to determine a maximum-likelihood path through a convolutional encoder, comprising:

a parallel implementation to prefetch previous optimal paths of two states from an optimal path memory and fetch traceback path width data bits from a path memory that is appended with data bits to provide an entire optimal path leading up to that path for each state.

Cancelled

27(New). The method of claim 26 further comprising:

sharing address generators for the optimal path memory and the path memory.

Cancelled

28(New). The method of claim 26, further comprising:

receiving a new symbol by the convolutional encoder; and
appending a new bit to the optimal path stored in the optimal path memory for each new symbol received.